

DN	Coupling Width (W) (mm)	Min.Outside diameter of Pipe (OD) (mm)	Max.Outside diameter of Pipe (OD) (mm)	Min. Inside diameter of Pipe (ID) (mm)	Max. Inside diameter of Pipe (ID) (mm)	Calibration length of Pipe (CL) (mm)	Chamfering angle
300	220	323,5	324,5	310,3	316,1	155-160	20 °
350	220	376,0	377,0	360,8	367,2	155-160	20 °
400	242	427,0	428,0	410,0	417,0	155-160	20 °
450	242	475,3	476,3	456,3	464,1	155-160	20 °
500	242	530,5	531,0	509,5	517,4	155-160	20 °
600	242	632,5	633,5	608,1	617,7	155-160	20 °
700	260	718,0	719,0	689,6	701,4	155-160	20 °
800	260	820,0	821,0	788,0	800,8	155-160	20 °
900	260	924,0	925,0	888,4	902,4	155-160	20 °
1000	260	1026,5	1027,5	987,1	1002,5	155-160	20 °
1100	260	1125,0	1126,0	1081,6	1098,4	155-160	20 °
1200	260	1227,0	1228,0	1180,0	1198,0	155-160	20 °
1300	260	1331,0	1332,0	1280,4	1299,6	155-160	20 °
1400	275	1433,0	1434,0	1378,6	1399,0	155-160	20 °
1500	275	1536,0	1537,0	1478,2	1500,4	155-160	20 °
1600	275	1639,0	1640,0	1577,4	1601,0	155-160	20 °
1700	275	1739,0	1740,0	1673,8	1698,4	155-160	20 °
1800	275	1842,0	1843,0	1773,0	1799,0	155-160	20 °
1900	275	1943,0	1944,0	1870,4	1897,6	155-160	20 °
2000	275	2045,5	2046,5	1969,3	1997,7	155-160	20 °
2100	275	2148,0	2149,0	2068,0	2097,6	155-160	20 °
2200	275	2250,0	2251,0	2166,4	2197,2	155-160	20 °
2300	275	2353,4	2354,4	2266,2	2298,2	155-160	20 °
2400	275	2454,5	2455,5	2363,7	2396,7	155-160	20 °

